

POS	COLOR	STRIPE	STRIPE	GΑ	DESCRIPTION
1	BLACK			10	MAIN GROUND
2	YELLOW			16	BLOWER (SW TO UNIT)
3	DKBLUE	BLACK		16	FLOOR LIGHTS (SW TO LIGHTS)
4	GREY	WHITE		16	NAVIGATION LIGHTS (SW TO LTS)
5	ORANGE	WHITE		16	HORN (SW TO UNIT)
6	GREY	RED		16	ANCHOR LIGHTS (SW TO LIGHTS)
7	BROWN			16	BILGE PUMP (SW TO UNIT)
8	PINK			16	FUEL SENDER (SNDR TO GAUGE)
9	LTGREEN			8	FUEL TANK BONDING
10	BROWN			16	BILGE PUMP (AUTOMATIC)
11	COPPER			20	RIGHT REAR SPKR +
12	SILVER			20	RIGHT REAR SPKR -
13	COPPER			20	RIGHT FRONT SPKR +
14	SILVER			20	RIGHT FRONT SPKR —
15	COPPER			20	LEFT FRONT SPKR +
16	SIL VER			20	LEFT FRONT SPKR -
17	COPPER			20	LEFT REAR SPKR +
18	SILVER			20	LEFT REAR SPKR -
19	ORANGE	BLACK		16	MNDSHIELD WIPER
20	ORANGE	BLUE		16	MPER (BKR TO SW)
	RED				12 VOLTS + (SAFETY SW TO IGN, BRKR.)
22	GREY	BLACK		16	COURTESY LIGHT (BKR TO SW)
23	DKBLUE			16	PANEL LIGHTS (SW TO LIGHTS)
24	PURPLE			16	IGNITION (SW TO RUN CIRCUIT)
25	BROWN	WHITE		16	BILGE PUMP (BKR TO SW)
26	ORANGE			16	HORN (BKR TO SW)
27	YELLOW	BLACK		16	BLOWER (BKR TO SW)
28	RED			10	12 VOLTS + (ENG TO DASH)
29	YELLOW	RED		16	IGNITION (SW TO STARTER)
30	LTBLUE			16	OIL PRESSURE SENDER
31	PURPLE	WHITE		16	TRIM GAUGE SENDER
32	GREY			16	IGN. COIL TO TACHOMETER
33	TAN			16	WATER TEMPERATURE SENDER
34	TAN	BLUE		16	ENG. AUDIBLE ALARM SENDERS
35	YELLOW	RED		16	IGN. (NEUT. SFTY. SW. TO IGN.)
36	BLACK			16	SECONDARY GROUND

NOTES:

1)SPOT BIND WITH BLACK TAPE EVERY 12"

2)DIMENSIONS INCLUDE TERMINAL ENDS.

3)CONSTRUCTION OF INCLUDED CONDUCTORS SHALL BE RATED AT 105°C AND CONFORM TO SAE JII28 AND J378 JUN84.

4)ADD LABLES WHERE SHOWN

5)SECONDARY GROUNDS TO BE TAKEN FROM #1 GROUND.

ΠΠΕ:	THUNDERBIRD PRODUCTS
FALCON 2270	P.O. BOX 1003
WIRING DIAGRAM	DECATUR, IN., 46733-5003
DATE: 2/23/94 DR. BY: JRE	(219) 724-9111

